



SPECIFICATION

Input Voltage [V]	220-240VAC
Output Voltage [V]	36VDC
Output Current[mA] at 230V	700mA 50/60HZ
Operating frequency [KHz]	>40
Lamp Wattage [W]	30W(+10%/-15%)
Operating Wattage [W]	28.8W
LED BRAND	BRIDGELUX
DRIVER	External Driver
Lumen output [lm]	2000
MAX Luminous Intensity (CD)	130 lux at 3m Height
Power Factor & DF	0.81 DF 0.85
CCT(K)	3CCT 3000-3500-4000K 80Ra
Dimmable	TRIAC Dimmable
Beam Anlge	10°-50° changeable
Size (mm)	D80*H215mm
Material	ALUMINUM HOUSING
Operating temp range (°C)	-30 to +45 °C
Humidity	10%-50%
Warranty	3 Years
Equal light	30W Metal Halide
WEIGHT(KGS)	0.7
PCS/CTN	20
CTN SIZE (CM)	47*38*29
Package	white box +netural packing

Product Features

- . Perfect low energy replacement for 30W Metal Halide
- . Anti-glare and eye friendly with UGR<19
- . Energy saving of up to 80% compared with traditional lamp
- . Impressive 30000 hours lamp life reduces re-lamping costs
- . Light holder being adjustalbe 350°
- . Triac Dimmable with 3CCT color Changeable ,No flicker
- . Zoom design ,Beam Angle changeable from 10° to 50°

